



LENNOX BATHROOM LTD

25 GREENMOUNT DR, EAST TAMAKI

AUCKLAND 2013

PHONE: +64 9 2710168

Lennox Shower Tray BPIR Declaration

Version A1 (08/24)

Designated building product: Class 1

Declaration

Lennox Bathroom Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name: Lennox Shower Tray

Identifier: JBL: RGM/RF/RAM

Description

The shower tray is made from ABS fibreglass and new finish, features a 50mm high continuous 20mm upstands to be installed against a wall. Sanitary Grade Acrylic features a high gloss surface for ease of cleaning.

The surface of the shower tray is thoughtfully designed with a non-slip texture, ensuring a secure and safe showering experience, with transparent protective film.

Square 2 sides upstand sizes: 900x900, 1000x1000

Round 2 sides upstand sizes: 800x800, 900x900, 1000x1000

Angle 2 sides upstand sizes: 900x900, 1000x1000

Square/Rectangle 4 sides upstand sizes: 800x800, 900x900, 1000x800, 1000x1000, 900x750, 900x800, 1000x900, 1100x750, 1200x800, 1200x900, 1200x1000

All sizes are nominal and specific availability varies according to the choose range.

Scope of Use

For interior installations in residential buildings, with timber or concrete flooring.

Install as a complete Acrylic Shower Enclosure (comprising Acrylic Shower Tray, Shower Liner & Shower Door or return if applicable) or as a Tile Option Shower Enclosure (comprising Shower Door Set or return if applicable only - Waterproofing & Tiles are not included).

Waste / drain holes are located in the centre of the either centrally or in the rear corner of the Lennox Shower Trays and must be fitted with the Hi Flow Waste which have standard DN40 waste outlets. Hot water must be supplied to this sanitary fixture via adjacent tapware.

Condition of Use

Lennox Bathroom Shower Trays must be installed and maintained in accordance with our supplied instructions, and must be fully supported and installed level. The substrate must not have been previously plastered, sealed or painted.

Special attention must be paid to the specific requirement for each joint - please refer to the installation instructions for further information.

The tapware & waste must be installed by a Registered Plumber. The maximum permitted temperature of water at the shower outlet is 50 degrees Celsius.

Relevant Building Code

B2 Durability — B2.3.1 (c)

E3 Internal moisture — E3.3.5, E3.3.6

F2 Hazardous building materials — F2.3.1, F2.3.3

G1 Personal Hygiene — G1.3.2 G12

G13 Foul Water

Statement of Contributions to Compliance

B2 Durability	Lennox bathroom Shower Tray have a durability of at least 2 years, when installed and maintained in accordance with our supplied instructions.
E3 Internal moisture	Surfaces of this product likely to be splashed or become contaminated during the intended use of the building, it's impervious and easily cleaned. The trays are made from ABS fibreglass and particles board, and are constructed with 50mm profile continuous with 20mm moulded upstand on each side to be installed against a wall.
F2 Hazardous building materials	This product is constructed of materials that will not emit harmful concentrations of substances from exposed surfaces.
G1 Personal Hygiene	Lennox Shower Tray must be provided with hot water to satisfy the intended usage of personal bathing (note - tapware not included).

G13 Foul Water	when water-borne disposal is used. This product is a sanitary fixture constructed and designed to be installed that facilitates sanitation and allow effective cleaning.
-----------------------	--

Supporting Documents

The following additional documentation supports the above statements:

Installation Instructions

<https://drive.google.com/file/d/1wb5hqHVCi12rtnJo9Oesm2GOLqV5fAR1/view?usp=sharing>

Warranty Statements:

https://www.lennoxbathroom.co.nz/akl/index.php?route=information/information&information_id=5

Maintenance Requirements:

Cleaning Recommendations: We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product. warranty. Refer to Warranty Conditions.

https://www.lennoxbathroom.co.nz/akl/index.php?route=information/information&information_id=5

For further information supporting Lennox Bathroom Shower Tray claims refer to our website.

Contact Details

Manufacture Location	China
Manufacture	Blue Skies NZ Trading Ltd Approved Manufacture
Legal and trading name of importer	Blue Skies NZ Trading Ltd
Address for Service	25 Greenmount Drive, East Tamaki, Auckland
Importer website	https://www.lennoxbathroom.co.nz/akl/
Importer email	info@lennoxbathroom.co.nz
Importer phone number	092710168
Importer NZBN	9429050516469